

Amphenol®



Photo: Coupling nut shown removed from plug. Connector can be ordered with or without coupling nut.

Amphenol® RPT Rugged Miniature Cylindrical Connectors

Amphenol® RPT Ruggedized Miniature Connectors

Designed with a stronger shell and reinforced keyway to perform in the harsh environments of the Geophysical Market.

- Machined shells for increased strength; 3 point bayonet coupling
- IP67 rated
- Anodized (nonconductive) shells for greater salt, corrosion and abrasion resistance
- Coupling nuts with or without round detent holes
- Solder contacts
- Available currently in shell sizes 16 & 20

RPT Connector Performance

Temperature rating: -55°C min., 125°C max.

Salt spray: 48 hr. unmated

Meets environmental requirements of MIL-C-26482G

Not intermateable with MIL-C-26482, Series 1

RPT Connector How to Order

Ordering procedure is illustrated by coded part number RPT05E16-8S(005) as shown below:

RPT 05 E 16-8 S (005)
 1 2 3 4 5 6

1. Connector Type

RPT designates Amphenol Rugged Miniature Cylindrical Connectors with bayonet coupling


2. Shell Style

- 04 designates in-line receptacle
- 05 designates cable plug with coupling nut, less hardware
- 45 designates cable plug without coupling nut, less hardware

- (consult Amphenol Industrial for availability of other shell styles)
- 3. Service Class
"E" designates environmental resisting connector
- 4. Shell Size and Insert Arrangement
16-8 (Shell size 16 with 8 size. 16 contacts)
20-16 (Shell size 20 with 16 size. 16 contacts)
(consult Amphenol Industrial for availability of other insert arrangements)
- 5. Contact Type
P designates pin, S designates socket
- 6. Plating Suffix
(Anodized)


RPT Connector Shell Styles

In-Line Receptacle.....RPT04*



Shell Size	L Max.	V Thread Plated Class 2A	S ±.016	SS Dia. +.000 -0.016
16	1.031	1.000-20 UNEF	1.410	1.297
20	1.188	1.250-18 UNEF	1.630	1.510

Cable Plug with Coupling Nut.....RPT05*



Shell Size	A +.000 -0.005	L Ref.	Q Ref.	V Thread Plated Class 2A	S Dia. Max.
16	1.174	.916	.947	1.000-20 UNEF	1.500
20	1.390	1.069	1.099	1.250-18 UNEF	1.700

Cable Plug without Coupling Nut... RPT45*





Shell Size	Coupling Nut Part Number Purchased Separately	
	Without Detent Holes	With Detent Holes
16	RPTCN-165	RPTCN-H165
20	RPTCN-205	RPTCN-H205

*To complete order number see how to order on front.

All dimensions for reference only.

For availability of wall mount receptacle style or jam nut receptacle style connectors, and additional insert arrangements, consult Amphenol Industrial.

Insert Availability



Insert Arrangement	16-8	Insert Arrangement	20-16
Service Rating	11	Service Rating	11
Number of Contacts	8	Number of Contacts	16
Contact Size	16	Contact Size	16

Also see Amphenol Miniature Cylindrical Connectors, MIL-C-26482, Series 1 (catalog 12-070-15).
 Also see Amphenol Aerospace and Industrial Product Overview catalog SL-100.

Notice: Specifications are subject to change without notice. Contact your nearest Amphenol Corporation Sales Office for the latest specifications. All statements, information and data given herein are believed to be accurate and reliable but are presented without guarantee, warranty, or responsibility of any kind, expressed or implied. Statements of suggestions concerning possible use of our products are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe any patent. The user should assume that all safety measures are indicated or that other measures may not be required. Specifications are typical and may not apply to all connectors.

For further information on your individual application requirements, contact: Amphenol Corporation

North America:
 Amphenol Industrial Operations
 180 N. Freeport Drive, Plant 4
 Nogales, AZ 85621
 Tel: (520) 285-5130
 Fax: (520) 285-5134

Email: rpdrizzini@amphenol-aio.com

Europe:
 Amphenol Industrial Operations Europe
 Via Barbaiana 5
 1-20020 Lainate (MI) Italy
 Tel: +39 02 93254.204
 Fax: +39 02 93254.444

Email: info@amphenol-aio.com

Middle East:
 Amphenol Middle East Enterprises FZE
 Office C-37 PO Box 21107
 Ajman Free Zone, UAE
 Tel: +9716-7422494
 Fax: +9716-7422941

Email: ameezfe@eim.ae

Asia:
 Amphenol Technology Shenzhen Ltd
 Block 5 Fuan 2nd Industrial Park
 Dayang Rd, Fuyong Baoan
 Baoan, Shenzhen, China 518103
 Tel: +86 755 2881 8389
 Fax: +86 755 2991 8310
 Email: yb.zhu@amphenol-industrial.com